



Castrol Transmax Dual

Dual Clutch Fluid

Description

Castrol Transmax Dual is a full synthetic SAE 75W dual clutch transmission fluid.

Advantages

- Excellent synchroniser and clutch performance due to balanced frictional characteristics
- Excellent thermal and oxidative stability
- Exceptional cold flow properties
- Operating temperature reduction through reduced friction
- Very good extreme pressure (EP) anti-pitting behaviour
- High shear resistance - constant viscosity during oil life
- Good seal compatibility

Typical Characteristics

Name	Method	Units	Castrol Transmax Dual
Colour	Visual	-	green
Pour Point	DIN-ISO 3016	°C	-72
Density @ 15C	DIN EN ISO 12185	g/ml	0.8376
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.2
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	35.5
Viscosity Index	DIN ISO 2909	None	166
Viscosity, Brookfield @ -40C	DIN 51398	mPa.s (cP)	7500

Product Performance Claims

- Ford WSS-M2C-936-A (Dual Clutch)
- Volvo, Chrysler (Europe), Mitsubishi
- VW G 052 529 (for Audi applications)
- Castrol Recommendation for VW, Seat, Skoda 6-speed Dual Clutch Transmission (DSG)

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Transmax Dual

11 Jun 2013

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0845 6008125 Technical Enquiries: 0845 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk