

CATENERA FLUID FT 2

Escalator chain oil



Benefits for your application

- Tried and tested oil for escalator chains
- Good wear protection
- Good corrosion protection

Description

CATENERA FLUID FT 2 is a mineral oil based lubricant for escalator chains offering good wear and corrosion protection.

When using automatic systems please observe the maximum viscosity specified by the manufacturer.

Application

CATENERA FLUID FT 2 has been especially designed for the lubrication of chains in escalators and passenger conveyors.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Application notes

CATENERA FLUID FT 2 can be applied by drip-feed or automatic systems, oil feeders or brush.

Pack sizes	CATENERA FLUID FT 2
Canister 5 l	+
Canister 20 l	+

Product data	CATENERA FLUID FT 2
Article number	030082
Lower service temperature	-20 °C / -4 °F
Upper service temperature	100 °C / 212 °F
Colour space	brown
Density, DIN 51757, 20 °C	approx. 0.89 g/cm ³
Flash point, DIN EN ISO 2592, Cleveland, open-cup apparatus	>= 200 °C
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 115 mm ² /s
Pour point, DIN ISO 3016	<= -20 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months



CATENERA FLUID FT 2

Escalator chain oil



Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.